

## PRODUCTS / SWIVELS MODELS







Our swivels are made of quality steel, with swivel part mounted on axial roller and driven with ball or roller bearings.

They are sealed and protected with zinc plating and used in applications of suspended or tightening parts which have to turn: cranes, derrick, drilling machines, power lines stretching and steel cables dock crane.

On request:

- Swivel joints with higher flow rates.
- Customer's joint sizes.

Approx. dimensions (mm)

Fixed Male	Code no.	Load capacity (t)	Code no.	Load capacity (t)	Fixed Female
	MG - 2	2	FG - 2	2	
	MG - 3	3	FG - 3	3	
	MG - 5	5	FG - 5	5	
	MG - 7.5	7.5	FG - 7.5	7.5	
	MG - 10	10	FG - 10	10	
	MG - 15	15	FG - 15	15	
	MG - 20	20	FG - 20	20	
	MG - 25	25	FG - 25	25	
	MM - 2	2	FM - 2	2	
	MM - 3	3	FM - 3	3	
	MM - 5	5	FM - 5	5	
	MM - 7.5	7.5	FM - 7.5	7.5	
	MM - 10	10	FM - 10	10	
	MM - 15	15	FM - 15	15	
	MM - 20	20	FM - 20	20	
	MM - 25	25	FM - 25	25	
	MF - 2	2	FF - 2	2	
	MF - 3	3	FF - 3	3	
	MF - 5	5	FF - 5	5	
	MF - 7.5	7.5	FF - 7.5	7.5	
	MF - 10	10	FF - 10	10	
	MF - 15	15	FF - 15	15	
	MF - 20	20	FF - 20	20	
	MF - 25	25	FF - 25	25	

**O.F.S. srl**

Via Virgilio, 8 - 20833 Birone di Giussano (MB) Italy-Tel + 39 0362 861437 - 310370 - Fax + 39 0362 310284  
 Cap. Soc.€10.000,00 i.v. - R.E.A. MB 1786223 - Reg.Imprese MB 02689650121 - P.IVA/C.F. (VAT) IT 02689650121